



A GIBRALTAR INDUSTRIES COMPANY



BLIJS I-JOIST SPACER

New Product

Usage:

» Provides 1/8" gap between double I-Joists in floor systems.

Features:

» Prevents double I-Joists from "rubbing" against each other

» Designed for use with double I-Joists

» Installs easily to top and bottom of I-Joist with a single nail

USP supplies quality products to build Stronger Safer Structures

Customer Service:
Burnsville, MN
Phone: 1-800-328-5934
Fax: 1-507-364-8762

Manufacturing:
Montgomery, MN
Livermore, CA
Largo, FL
Thornhill, Ontario

Warehouses:
Houston, TX
Lumberton, NJ

Materials: 16 gauge
Finish: G90 galvanizing

Installation:


- Install spacers near the ends and at third points along the span. Fasten to the top and bottom of I-Joist with (1) 10d nail.
- Spacing shall not exceed 8 feet.
- BLIJS spacers are not structurally rated.



Typical *BLIJS* installation



BLIJS



Go to www.uspconnectors.com/cad/ for Downloadable CAD drawings

USP Stock No.	Ref. No.	Steel Ga.	Fastener ¹ Schedule
BLIJS	-- --	16	(2) 10d

1) Minimum nail embedment shall be 1-1/2" for 10d nails.
Consult USP for pricing.