



HBPS58

SLOTTED BEARING PLATE

**New
Product**

Usage:

» Meets code requirements for plate washers used with braced wall line sills in seismic regions.

» Reduces sill plate cross grain bending.

Features:

» Greater load distribution than conventional washers.

» Plate design features an anchor bolt adjustment slot.

» 3" x 3" x 1/4" plate meet IRC & IBC requirements for seismic regions.

USP supplies quality products to build Stronger Safer Structures

Customer Service:
Burnsville, MN
Phone: 1-800-328-5934
Fax: 1-507-364-8762

Manufacturing:
Montgomery, MN
Livermore, CA
Largo, FL
Thornhill, Ontario

Warehouses:
Houston, TX
Lumberton, NJ

www.USPconnectors.com

Materials: See chart

Finish: None

Codes: IRC R602.11.1,
IBC 2305.3.11

Installation:

- Use with 5/8" diameter anchor bolt.
- Bolt holes are sized 1/16" larger than bolt diameter in chart.
- When used with braced wall line sills in seismic regions a standard cut washer is required between the nut and plate washer.



Typical *HBPS58* Installation



HBPS58

USP Stock No.	Ref. No.	Plate Thickness	Dimensions		Bolt Dia.	Ctn Qty
			W	L		
HBPS58	BPS5/8-3	1/4	3	3	5/8	50

Consult USP for pricing.