

CONCRETE ANCHORING SOLUTIONS for the 2006 IBC



DUC DUCTILE UNDERCUT ANCHORS

- TESTED TO ICC ES AC 193 & ACI 355.2
- QUALIFIED FOR USE IN CRACKED AND UNCRACKED CONCRETE
- DESIGN USING ACI 318-05, APPENDIX D
- ICC ES ESR 1970 FOR 2006 IBC
- CITY OF LA RR 25753
- FLORIDA BUILDING CODE FL4928 R-1
- DUCTILE TENSILE FAILURE - AVOIDS 2.5 IBC OVERSTRENGTH FACTOR FOR NON-DUCTILITY



**FIRST ANCHOR TO BE LISTED BY ICC ES
FOR USE IN CRACKED CONCRETE
WITH THE 2006 IBC.**

CIA-GEL 7000 EPOXY ANCHORING

- TESTED TO ICC ES AC 308
- QUALIFIED FOR USE IN UNCRACKED CONCRETE
- DESIGN USING ACI 318-05, APPENDIX D
- ICC ES ESR 1702 FOR MASONRY (2006 IBC)
- ICC ES ESR FOR CONCRETE PENDING
- CITY OF LA RR 25113 & 25029
- FLORIDA BUILDING CODE FL4928 R-1
- NSF 61 DRINKING WATER APPROVAL
- DOT LISTED IN 23 STATES

**CIA-GEL 7000 IS BACKED BY
OVER A DECADE OF SOLID
FIELD PROVEN PERFORMANCE.**



A GIBRALTAR INDUSTRIES COMPANY

WHAT THE PROFESSIONALS USE

COVERT
OPERATIONS
EPOXY ANCHORING & CRACK INJECTION SYSTEMS

For further information call 1-800-328-5934, or visit www.USPconnectors.com